









Installation Procedure

- 1. Clean Select a highly visible, completely flat surface on the case, preferably the outside lid of a notebook or the front panel of a desktop PC. Clean the location with the alcohol swab provided. Let the alcohol dry completely. Peel the protective backing from the plate.
- 2. Apply Gel Apply a tiny drop of gel near each corner of the plate, and a thin strip of gel along the entire width of the tattoo so the gel will cover the whole tattoo area when the plate is applied to the surface of the case. Careful—too much gel will ooze out from under the plate!

Warning: Adhesive instantly bonds skin and can cause severe eye damage. Read caution statement on tube.

- **3. Apply Plate** Immediately place the plate on the case before the gel begins to set. Press firmly on all four corners of the plate until you obtain a firm bond (approximately 20 seconds). Caution: the plate may slide a bit before bonding completely. Then press firmly all over the plate area to ensure a flat, airtight bond.
- **4.** If Excess Gel If excess gel appears at the edges of the plate, remove it immediately by gently scooping it away with the protective backing you peeled from the back of the plate in Step 1.
- **5. Apply Red Sticker** Apply the red warning sticker next to the plate.
- **6. Register** Log onto **www.stoptheft.com** and register your information and STOP identification number. This information will allow us to contact you on the chance that your equipment is lost or stolen.

Attention: When you sell or return your equipment, do not remove the STOP plate! This will reveal the "Stolen Property" tattoo and render the equipment impossible to

Stolen Property 1-800-488-STOP

resell. Legitimate buyers of used equipment can re-register it for FREE at www.stoptheft.com/trackset. So that used equipment can be registered without having to contact you for verification, please send STOP the ID numbers of decommissioned equipment for our records.